



## CERTIFICATE OF TESTING

For the Account Of: Bru Textiles  
Satenrozen 2a  
B2550 Kontich  
Belgium  
Contact: Tineke Verbruggen

Client's Identification: FR-One Genii: Griflet~Gaheris~Geraint~Gorlois

**TEST PERFORMED** NY / NJ Port Authority Specifications Governing the Flammability of Drapery and Curtain Materials in Unsprinkled Areas (Appendix A) – 2010  
[FAR 25.853(a) Appendix F, as revised February 2, 1995 – 12 second vertical method]

**TEST RESULTS**

Specimen	Afterflame (s)	Char Length (in)
1	0	3.5
2	0	3.1
3	0	3.9
<b>Average Warp</b>	<b>0</b>	<b>3.5</b>
4	0	3.4
5	0	3.5
6	0	4.4
<b>Average Fill</b>	<b>0</b>	<b>3.7</b>

**Tested:**

- Initially
- After Laundering
- After Dry Cleaning

**NOTES**

**Test Conditions:** 70 ±2°F, 65 ±2% Relative Humidity

**ACCEPTANCE CRITERIA**


1. Average Burn Length cannot exceed **8 inches** maximum average.
2. Average Flame Time after removal of the flame source may not exceed **5 seconds**.

**CONCLUSION**

Based on the above Results and Acceptance Criteria, the item tested:

- Complies
- Does Not Comply

**CERTIFICATION** I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

  
\_\_\_\_\_  
Authorized Signature